

Transport Business Successfully Waterproofs Bridges

BITUTHENE® 5000 and SOLARSHIELD® 100 used in Expo Milan 2015 project



Project	EXPO Milano 2015
Owner	EXPO 2015
Engineer	Marco Acquati Engineer (MM)
General Contractor	Ing. Mantovani SpA
GCP Solutions	BITUTHENE® waterproofing, SOLARSHIELD® waterproofing

Project Profile

Supporting 20 million visitors

Expo Milano 2015 was a non-commercial exhibition site, which was open from May 1 to October 31, 2015. The exhibition site covered 1 million square meters and welcomed over 20 million visitors, hosted over 130 participants, and ran for 184 days.

The project involved bridge construction of several small trafficable bridges linked to the main EXPO deck, which crossed over an artificial stream.

A self-adhesive membrane solution was proposed to satisfy the needs of the bridge construction project. The proposal consisted of both BITUTHENE®5000 and SOLARSHIELD®100 membranes to the bridge deck areas.

"A self-adhesive membrane solution was proposed to satisfy the needs of the bridge construction project. The proposal consisted of both Bituthene® 5000 and Solarshield® 100 membranes to the bridge deck areas."

Delivering bridge deck waterproofing

The transport business responsible for the project required a low-thickness waterproofing membrane, which offered protection to the bridge decks and also met the criteria defined by the Milan Metropolitan office. The chosen system had to offer resistance to hot asphalt, provide complete adhesion, and be easy to apply.

"The chosen system had to offer resistance to hot asphalt, provide complete adhesion, and be easy to apply."

Delivering unparalleled waterproof protection

GCP proposed a self-adhesive membrane solution to satisfy the needs of the car bridge construction project. The proposal consisted of both BITUTHENE®5000 and SOLARSHIELD®100 membranes to the bridge deck areas.

BITUTHENE®5000 is a preformed, cold applied sheet membrane that is 1.6mm thick overall, comprising of a self-adhesive rubber/bitumen compound, protected with a silicone release paper, with a polypropylene mesh carrier film and is supplied in 1.0m x 20.0m long rolls. SOLARSHIELD®100 is a robust, cold applied self-adhesive aluminum membrane, which can be used as a conformable solar reflective flashing or protection for exposed roofing membranes.

GCP's Blue360SM Field Advantage team provided ongoing site support, ensuring materials were applied according to the recommended installation guidelines. This value-added service was critical since no specialized applicator was involved

Blue 360SM Product Performance Advantage.

Because every project, large or small, deserves the best level of protection.

"This value-added service was critical since no specialized applicator was involved."

gcpat.com | North America Customer Service: 1 877-4AD-MIX1 (1 877-423-6491)

This document is only current as of the last updated date stated below and is valid only for use in the United States. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.com. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.